

150W constant Voltage-LS Series



■ Approve



Features

- Class II, SELV, Independent
- Input Voltage 220-240VAC
- Protections: SCP/OLP/OVP/OTP
- Power Factor: > 0.9
- Efficiency: ≥91%
- 5 years warranty

Applications

- LED strips


◆ Description

LS-150-XX LI1 is a 150W constant voltage LED driver that operates from 198-264Vac input with 24V output voltage. With it's compact dimensions from 268 x 45 x 30.5mm. It is easy to integrate in LED strips products.

To ensure trouble-free operation, protection is provided against output short circuit and over Load.

◆ Model code


LS-150-XX LI1




◆ Specification

Output	Constant Voltage	24±1VDC		48±1VDC	
	Current Range	0-6.25A		0-3.13A	
	Voltage Accuracy	±5%			
	Output HF current ripple(≥1KHz)	±5%			
	Output LF current ripple(≤120Hz)	±5%			
	SVM	≤0.4			
	Pst	≤1			
	Efficiency(Typ.)	≥91%			
Input	Rated input voltage	220-240VAC			
	Range of input voltage	198-264VAC			
	Frequency(Hz)	50/60 Hz			
	Power Factor	> 0.9			
	Input Current max	0.95A			
	Start-up time	< 0.5S			
	No Load Power	≤0.5W			
	THD (Typ.)	< 10%			
Protection	Over Load Protection	105-150% YES/Auto Resume			
	Over Voltage Protection	> 25.2Vdc		> 50.4Vdc	
		YES/Auto Resume			
	Short circuit Protection	YES/Auto Resume			
	Over Temperature Protection	YES/Auto Resume			
Environment	Operating Temperature	-20°C~~+45°C			
	Humidity	20%-90%RH			
	Tc	85°C			
	Storage Temperature	-20°C~~+60°C			
	Life time	> 50000h@Tc=80°C			
Surface	Dimension	268X45X30.5(LXWXH)mm			
Standards	EN61347- 1, EN61347-2- 13; IEC61347- 1, IEC61347-2- 13; EN61347- 1, EN61347-2- 13, EN62384; EN55015, EN61000-3-2, EN61000-3-3, EN61547; GB/T17743, GB17625. 1,GB19510. 1, GB19510. 14				
Others	ErP	EU 2019/2020			
	RoHS	RoHS (2011/65/EU) (EU)2015/863			
Note	1.All parameters not specially mentioned are measured at 240VAC input , full load and 25°C of ambient temperature. 2.Ripple & Noise are measured at 20MHz of bandwidth by using a 300mm twisted pair-wire terminated with a 0.1uF & 47 uF parallel capacitor.				

◆ Wiring diagram



◆ 2D diagram




◆ Wiring & Connections


Specification item		Value (Unit)
Input	Input wire cross-section	0.5...1.5 mm ²
	Input wire gauge.	16...20 AWG
	Input wire strip length	7...9mm
Output	Output wire cross-section	0.5...1.5 mm ²
	Output wire gauge.	16...20 AWG
	Output wire strip length	7...9mm

◆ Curve for LS-150-48 LI1


Lifetime vs. Temperature Curve




Efficiency vs. Load




Power Factor Characteristics



THD vs. Load



◆ Operating window



◆ Revision Updates

ITEM	BEFORE	AFTER	VERSION	DATE
Initial			A	2022/05/15

Tel: +86-0757-86256822, +86-0757-86256831

E-mail: sales@eaglerise.com

Website : <https://lighting.eaglerise.com>



EAGLERISE



Manual